

000-733 IBM certifications II

IBM IBM Certified Application Developer-DB29


Practice Exam: 000-733 Exams

Exam Number/Code: 000-733

Exam Name: IBM Certified Application Developer-DB29

Questions and Answers: 140 Q&As

([IBM certifications II](#))



Exam : [000-733](#)

"IBM Certified Application Developer-DB29", also known as 000-733 exam, is a IBM certification. With the complete collection of questions and answers, TestInside has assembled to take you through 140 Q&As to your 000-733 Exam preparation. In the 000-733 exam resources, you will cover every field and category in IBM Certification helping to ready you for your successful IBM Certification.

Quality and Value for the 000-733 Exam TestInside Practice Exams for IBM **IBM certifications II** Certification 000-733 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

TestInside provide the professional Q&A.

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 000-733 Exam.

000-733 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the IBM certifications II product experts, included the current newest 000-733 examination questions.

3. 100% Guarantee to Pass Your IBM certifications II exam and get your IBM certifications II Certification.

If you do not pass the IBM Certification 000-733 exam (IBM Certified Application Developer-DB29) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

use TestInside 000-733 Q&A ensure you pass the exam at your first try.

TestInside professional provide IBM certifications II 000-733 the newest Q&A, completely covers 000-733 test original topic. With our complete IBM certifications II resources, you will minimize your IBM certifications II cost and be ready to pass your 000-733 tests on Your First Try, 100% Money Back Guarantee included!

[IBM 000-733](#) Test belongs to one of the IBM certifications II certified test, if needs to obtain the IBM certifications II certificate, you also need to participate in other related test, the details you may visit the [IBM certifications II](#) certified topic, in there, you will see all related IBM certifications II certified subject of examination.

TestInside Testing Engine Features

Comprehensive questions and answers about 000-733 exam

000-733 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

000-733 exam questions updated on regular basis

Same type as the certification exams, 000-733 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 000-733 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : IBM 000-733

Title : IBM Certified Application Developer-DB29

1. An application running against a DB2 for AIX database needs to execute the following query:

```
SELECT t2.c2, t1.c3 FROM t1 INNER JOIN t2 ON t1.c1 = t2.c1
```

If table T1 resides in the DB2 for AIX database and table T2 resides in a DB2 for i5/OS database, which of the following DB2 object types must the identifier T2 represent in order for this SQL statement to run successfully?

- A. ALIAS
- B. NICKNAME
- C. SERVER TABLE
- D. TABLE WRAPPER

Answer: B

2. A table named ACTIVITY.LOG was created by executing the following statement:

```
CREATE TABLE activity.log (event VARCHAR(128), date DATE)
```

Then, a stored procedure named ACTIVITY.LOGEVENT was created by executing the following statement:

```
CREATE PROCEDURE activity.logEvent(IN stmtType CHAR(1))
```

```
LANGUAGE SQL
```

```
MainBody: BEGIN
```

```
DECLARE sqlerrm VARCHAR(256) DEFAULT '';
```

```
DECLARE ErrorIndicator CHAR(1) DEFAULT 'N';
```

```
SQLStmt: BEGIN
```

```
DECLARE CONTINUE HANDLER FOR SQLEXCEPTION
```

```
BEGIN
```

```
SET ErrorIndicator = 'Y';
```

```
END;
```

```
IF stmtType = 'I' THEN
```

```
INSERT INTO activity.log VALUES('Insert Operation Performed.', CURRENT_DATE);
```

```
ELSEIF stmtType = 'U' THEN
```

```
INSERT INTO activity.log VALUES('Update Operation Performed.', CURRENT_DATE);
```

```
ELSEIF stmtType = 'D' THEN I
```

```
NSERT INTO activity.log VALUES('Delete Operation Performed.', CURRENT_DATE);
```

```
ELSE
```

```
SET ErrorIndicator = 'Y';
```

```
END IF;
```

```
END SQLStmt;
```

```
IF ErrorIndicator = 'Y' THEN
```

```
SIGNAL SQLSTATE '70000' SET message_text = 'Could not update activity log.';
```

```
END IF;
```

```
END MainBody
```

User USER1 has the authority to access/manipulate data in the ACTIVITY.LOG table as well as to invoke the procedure ACTIVITY.LOGEVENT. If user USER1 executes the following commands:

```
CONNECT TO sample USER user1 USING ibmdb2;
```

```
DELETE FROM activity.log;
```

```
CALL activity.logEvent('I');
```

What will be the results?

- A. The string "Insert Operation Performed." and the system date will be written to the ACTIVITY.LOG table.
- B. The string "Update Operation Performed." and the system date will be written to the ACTIVITY.LOG table.
- C. The string "Delete Operation Performed." and the system date will be written to the ACTIVITY.LOG table.
- D. The error message 'SQL0438N Application raised error with diagnostic text: "Could not update activity log.". SQLSTATE=70000' will be generated.

Answer: D

3. After executing the following SQL statements:

```
CREATE TABLE tab1 (
col1 INT ,
col2 CHAR(1),
PRIMARY KEY(col1));
CREATE TABLE tab2 (
col1 INT ,
col2 CHAR(1),
FOREIGN KEY (col1) REFERENCES tab1(col1)
ON DELETE CASCADE
ON UPDATE NO ACTION );
INSERT INTO tab1 VALUES(1, 'A');
INSERT INTO tab1 VALUES(2, 'B');
INSERT INTO tab2 VALUES(3, 'A');
INSERT INTO tab2 VALUES(2, 'B');
UPDATE tab1 SET col1 = col1 + 1;
DELETE FROM tab1 WHERE col2 = 'B';
```

What values will be returned by the following SQL query?

```
SELECT col1, col2 FROM tab1 A.COL1 COL2 ===== 2 'B'
```

A. COL1 COL2

=====

2 'B'

B. COL1 COL2

=====

2 'A'

C. COL1 COL2

=====

1 'A'

2 'B'

D. COL1 COL2

=====

2 'A'

3 'B'

Answer: B

4. Which of the following SQL statements demonstrates the correct usage of a parameter marker?

- A. SELECT ? FROM SYSCAT.TABLES
- B. SELECT [] FROM SYSCAT.TABLES
- C. SELECT CAST(? AS INTEGER) FROM SYSCAT.TABLES
- D. SELECT CAST([] AS INTEGER) FROM SYSCAT.TABLES

Answer: C

5. Which of the following is a SQL stored procedure which will return a resultset containing ID, NAME, DEPT and JOB values out of the STAFF table?

- A. CREATE PROCEDURE result_set()
LANGUAGE SQL

```

BEGIN
SELECT id, name, dept, job
FROM staff;
END
B. CREATE PROCEDURE result_set
LANGUAGE SQL
RESULT SETS 1
BEGIN
SELECT id, name, dept, job
FROM staff;
END
C. CREATE PROCEDURE result_set
RESULT SETS 1
BEGIN
DECLARE c1 CURSOR FOR
SELECT id, name, dept, job
FROM staff;
OPEN C1;
END
D. CREATE PROCEDURE result_set()
LANGUAGE SQL
RESULT SETS 1
BEGIN
DECLARE c1 CURSOR WITH RETURN FOR
SELECT id, name, dept, job
FROM staff;
OPEN c1;
END

```

Answer: D

6. Which of the following ADO .NET providers is supported by IBM DB2 Add-ins for Visual Studio?

- A. OLE DB .NET Data Provider
- B. DB2 Data Provider for .NET
- C. ODBC Data Provider for .NET
- D. DB2 for i5/OS .NET Provider

Answer: B

7. Which of the following is a characteristic of an application that uses a Distributed Unit of Work (DUOW)?

- A. A single transaction can only read and/or modify data stored on one database server.
- B. Multiple transactions can only read and/or modify data stored on one database server.
- C. A single transaction can read and/or modify data stored across multiple database servers.
- D. Multiple transactions can read and/or modify data stored on multiple database servers provided each transaction only accesses a single server.

Answer: C

8. After installing the DB2 Express-C 9 it was discovered that the Development Workbench was not available. What was the reason for that?

- A. It must be installed separately.
- B. It is not supported with DB2 Express-C 9.
- C. Since it is a licensed tool, it must be purchased from IBM.
- D. Review the DB2 installation log for errors. Reinstall DB2 Express-C 9.

Answer: A

9. An SQL procedure has been developed with several inline SQL PL statements encapsulated in a dynamic compound SQL statement. The procedure had been tested and performed well. After making a change to the last SQL statement the procedure not only failed to complete, but did not produce output from any statements which were not modified. What is the best explanation for this behavior?

- A. The dynamic compound SQL is atomic.
- B. The procedure doesn't have any savepoints.
- C. The procedure has not been correctly re-cataloged.
- D. The dynamic compound SQL individual statements are logically dependent on each other.

Answer: A

10. What is the minimum privilege required to run a User Defined Function (UDF)?

- A. CALL
- B. EXECUTE
- C. SYSCTRL
- D. SYSMANT

Answer: B

11. Given the following table definition:

```
CREATE TABLE staff (  
id SMALLINT NOT NULL,  
name VARCHAR(9),  
dept SMALLINT,  
job CHAR(5))
```

Assuming that the following statements execute successfully:

```
Dim cmdStaff As DB2Command = cnDb2.CreateCommand()  
cmdStaff.CommandText = "SELECT name FROM staff WHERE (job = @job)"
```

Which of the following is the correct way to provide a value for the parameter marker used?

- A. cmdStaff.Parameters.Add("@job", "Mgr", CType(5, Char))
- B. cmdStaff.Parameters.Add("@job", "Mgr", DB2Type.Char, 5)
- C. cmdStaff.Parameters.Add(New DB2Parameter("@job", CType(5, Char)) cmdStaff.Parameters("@job").Value = "Mgr"
- D. cmdStaff.Parameters.Add(New DB2Parameter("@job", DB2Type.Char, 5) cmdStaff.Parameters("@job").Value = "Mgr"

Answer: D

12. Which of the following is the DB2 Data Provider for the .NET class that requires a database connection to be open?

- A. DB2DataSet
- B. DB2RecordSet
- C. DB2DataReader
- D. DB2DataAdapter

Answer: C

13. If the following code is executed in the order shown:

```
conDB2 As DB2Connection  
conDB2.ConnectionString = "Database=samplelx;UID=db2user;PWD=db2pwd;"  
conDB2.Open()
```

Which of the following statements is correct?

- A. An exception is thrown because the server name has not been specified.
- B. An exception is thrown because the server name and the port have not been specified.
- C. The execution is successful provided the host name SAMPLEX has been previously defined in the local hosts table.
- D. The execution is successful provided the database alias SAMPLEX has been previously defined in the local

database catalog.

Answer: D

14. Table EMPLOYEE contains the following rows:

EMPNO FIRSTNME LASTNAME WORKDEPT

000010 CHRISTINE HAAS A00

000020 MICHAEL THOMPSON B01

000030 SALLY KWAN C01

The isolation level for Application 1 is set to CS and autocommit is disabled. The isolation level for Application 2 is set to CS and the autocommit is enabled.

The following statements are executed in sequence:

Application 1:

```
DECLARE c1 CURSOR FOR SELECT * FROM employee ORDER BY empno
```

```
OPEN C1
```

```
FETCH C1
```

```
FETCH C1
```

Application 2:

```
UPDATE employee SET lastname = 'MILLFORD' WHERE empno = '000020'
```

Which of the following statements is correct?

A. The UPDATE succeeds because Application 2 runs with autocommit enabled so no row level locks are necessary for the update.

B. The UPDATE succeeds because Application 1 holds a row level lock that is compatible with the lock required by Application 2.

C. The UPDATE fails because Application 1 holds a row level read lock that is in conflict with the lock required by Application 2.C.

D. The UPDATE fails because the row level locks held by Application 1 have been escalated to table lock so updates by other connections are disallowed.

Answer: B

15. Parameter markers are NOT permitted for which of the following statements?

A. CALL

B. DELETE

C. EXECUTE IMMEDIATE

D. SET CURRENT SQLID

Answer: C

16. Given following table:

EMP

EMPNO NAME DEPTNO SALARY

=====

0010 JOSH D95 30000

0020 JENNA D98 25000

0030 DYLAN D95 10000

0040 TRACY D90 33000

and the following trigger definition:

```
CREATE TRIGGER track_chgs
```

```
AFTER UPDATE OF salary, name, empno ON emp
```

```
REFERENCING NEW_TABLE AS ntable
```

```
FOR EACH STATEMENT MODE DB2SQL
```

```
BEGIN ATOMIC
```

INSERT INTO changes

SELECT empno, CURRENT_TIMESTAMP FROM ntable;

END;

After executing the following SQL statements:

DELETE FROM changes;

UPDATE emp SET deptno = 'D98' WHERE deptno = 'D95';

INSERT INTO emp VALUES('0050', 'KEN', 'D90', 35000);

UPDATE emp SET salary = salary - 500 WHERE salary > 35000;

UPDATE emp SET salary = salary + 1000 WHERE salary <= 25000;

What value will be returned by this query?

SELECT count(*) FROM changes

A. 2

B. 3

C. 4

D. 6

Answer: A

17. Which of the following restrictions pertains to embedded SQL external routines?

A. Environment variables with names that start with 'DB2' are not allowed.

B. Executing statements or commands that are connection related is not allowed.

C. Environment variable values that were set before the DB2 database manager is started are not available.

D. When returning result sets from external nested stored procedures, a cursor cannot be opened with the same name on multiple nesting levels.

Answer: B

18. A .NET application executes a SQL request invoking the DB2Command.ExecuteReader method and a syntax error exception is thrown. Which of the following properties contains the SQLCode for this syntax error?

A. DB2Error.SQLCode

B. SQLError.SQLCode

C. DB2Exception.SQLCode

D. SQLException.SQLCode

Answer: A

19. Given the following table and view definitions:

CREATE TABLE city (

cityid INT GENERATED ALWAYS AS IDENTITY ,

city_name CHAR(10),

state_code CHAR(2) CHECK(state_code IN ('CA','IL','NY','OH','TX'));

CREATE VIEW city_view AS (

SELECT city_name||','||state_code AS fullname FROM city

WHERE state_code NOT IN ('OH','IL'));

and the following trigger definition:

CREATE TRIGGER city_viewInput

INSTEAD OF INSERT ON city_view

REFERENCING NEW AS n

FOR EACH ROW MODE DB2SQL

BEGIN ATOMIC

DECLARE delim INT;

SET delim = LOCATE(',', n.fullname);

INSERT INTO city(city_name,state_code)

VALUES(SUBSTR(n.fullname, 1, delim - 1), SUBSTR(n.fullname, delim + 1, 2));

END;

If the following SQL statements are executed:

```
INSERT INTO city VALUES(DEFAULT,'San Jose','CA') ;
INSERT INTO city_view VALUES('Chicago,IL');
INSERT INTO city VALUES(DEFAULT,'Detroit','MI');
INSERT INTO city VALUES(DEFAULT,'Austin','TX');
INSERT INTO city_view VALUES('Denver,CO');
```

How many rows will be returned by the following query:

```
SELECT * FROM city
```

- A. 1
- B. 2
- C. 3
- D. 4

Answer: C

20. Two OLTP applications run concurrently but frequent locking occurs which requires a fix to be applied. Application A inserts rows into the table T1. Application B submits several queries against the table with a Cursor Stability isolation level. What would be the best course of action to improve the system's concurrency and performance?

- A. Application B should be changed to access a view of table T1.
- B. Application B should be changed to a Read Stability isolation level.
- C. Application A should be changed to perform a commit after each INSERT operation.
- D. Application A should be changed to include the NOT WITH HOLD clause on each INSERT operation.

Answer: C

[More 000-733 Information](#)

Related 000-733 Exams

- [000-331](#) Power Systems Sales for AIX and Linux
- [000-253](#) Test253. IBM Web S.App.Svr.Ntwork Development V6.1.Core Admn
- [000-903](#) IBM Tivoli Netcool/xSM
- [000-926](#) IBM Certified Deployment Professional-Maximo V6 ITSM
- [000-351](#) ib m eserver i5 iseries single system adminsitration v5r3
- [000-647](#) Rational Performance Tester
- [000-833](#) Object Oriented Analysis and Design-Part1(Analysis)
- [000-443](#) db2 content manager v8.3
- [000-807](#) Test 807, Web Services Dev for IBMWeb Sphere App Server V6.1
- [000-806](#) IBM Test 806, IBMWeb Sphere Ap Svr Ntwk Deploy V6.1 Adv Admn
- [000-631](#) rational-clearcase for unix
- [000-918](#) System Administration for IBM Informix Dynamic Server V11
- [000-284](#) Test 284, IBM Wbs. DataPower SOA Appliances, Fimware v3.6.0
- [000-649](#) Rarional Software Architect
- [000-798](#) ib m tivoli monitoring for transaction perf v5.2 implement
- [000-971](#) System i Administrator V5.07.11
- [000-637](#) rational-requirements management with use cases-part2
- [000-664](#) Test664.SOA Fundamentals
- [000-484](#) enterprise connectivity with j2ee v1.3
- [000-635](#) rational-fundamentals of rational rose

Other IBM Exams

- [000-990](#)
- [000-355](#)
- [000-630](#)
- [000-256](#)
- [000-M32](#)
- [000-419](#)
- [000-002](#)
- [000-866](#)

000-774

000-815

000-022

000-207

000-851

000-779

000-870

LOT-955

000-913

000-M45

000-717

000-P01