

642-432 IP Communications Cisco Cisco Voice Over IP

Practice Exam: 642-432 Exams

Exam Number/Code: 642-432

Exam Name: Cisco Voice Over IP

Questions and Answers: 97 Q&As

([IP Communications](#))



Exam : [642-432](#)

"Cisco Voice Over IP", also known as 642-432 exam, is a Cisco certification. With the complete collection of questions and answers, TestInside has assembled to take you through 97 Q&As to your 642-432 Exam preparation. In the 642-432 exam resources, you will cover every field and category in Cisco Certification helping to ready you for your successful Cisco Certification.

Quality and Value for the 642-432 Exam TestInside Practice Exams for Cisco **IP Communications** Certification 642-432 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

TestInside provide the professional Q&A.

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 642-432 Exam.

642-432 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the IP Communications product experts, included the current newest 642-432 examination questions.

3. 100% Guarantee to Pass Your IP Communications exam and get your IP Communications Certification.

If you do not pass the Cisco Certification 642-432 exam (Cisco Voice Over IP) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

use TestInside 642-432 Q&A ensure you pass the exam at your first try.

TestInside professional provide IP Communications 642-432 the newest Q&A, completely covers 642-432 test original topic. With our complete IP Communications resources, you will minimize your IP Communications cost and be ready to pass your 642-432 tests on Your First Try, 100% Money Back Guarantee included!

[Cisco 642-432](#) Test belongs to one of the IP Communications certified test, if needs to obtain the IP Communications certificate, you also need to participate in other related test, the details you may visit the [IP Communications](#) certified topic, in there, you will see all related IP Communications certified subject of examination.

TestInside Testing Engine Features

Comprehensive questions and answers about 642-432 exam

642-432 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

642-432 exam questions updated on regular basis

Same type as the certification exams, 642-432 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 642-432 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : Cisco 642-432

Title : Cisco(r) Voice Over IP

1. In a VoIP environment when speech samples are framed every 20 ms, a payload of 20 bytes is generated. Assuming a total packet length of 60 bytes, what is the length of the packet header if cRTP is deployed without redundancy checks?

- A. 1 byte
- B. 2 bytes
- C. 3 bytes
- D. 4 bytes
- E. 20 bytes
- F. 40 bytes

Answer: B

2. In T1 CAS, where are the signaling states and control features carried for Super Frame robbed-bit signaling?

- A. 6th and 12th frame
- B. 6th, 12th, 18th, and 24th frame
- C. the first and seventeenth time slot
- D. the first and sixteenth time slot

Answer: A

3. You are working with a potential customer that would like to integrate its existing PBX telephone system into its IP network. The accompanying figure shows that the customer has two offices that need to be connected to the IP network so that the customer can exchange telephone calls without using the PSTN. Both PBXs use an in-band signaling type.

Which signaling type will allow you to support your customer?

- A. QSIG
- B. CCS
- C. CAS
- D. T-CCS
- E. E&M
- F. FXO

Answer: C

4. You are working with your customer in their lab to test the effect of jitter on voice quality. You have set the maximum playout delay to 40 ms on the voice enabled routers. What will be the impact on voice quality if after severe congestion the playout buffer empties and the source sends packets to the buffer faster than they are leaving?

- A. There will be no noticeable drop in quality.
- B. The jitter buffer will adapt to the faster-arriving packets by expanding the buffer size.
- C. The jitter buffer will speed up delivery of packets to the DSP so that packets are not dropped.
- D. After the jitter buffer fills up, subsequent packets are discarded.

Answer: D

5. Examine the output.

Your customer has sent you their MGCP gateway configuration. They are unable to get the gateway to communicate with the call agent. What command needs to be inserted to resolve the problem?

- A. ccm-manager mgcp 172.16.1.1
- B. mgcp call-agent 172.16.1.1
- C. application MGCPAPP 172.16.1.1
- D. mgcp 5036 172.16.1.1

Answer: B

6. You are working with a potential customer that would like to integrate its existing PBX telephone system into its IP network. The accompanying figure shows that the customer has two offices that need to be connected to the IP network so that the customer can exchange telephone calls without using the PSTN. Both PBXs are currently connected to T1 ISDN circuits.

Which signaling type will allow you to support your customer?

- A. QSIG
- B. CCS
- C. CAS
- D. T-CCS
- E. E&M
- F. FXO

Answer: A

7. You have a customer that is interested in determining the number of VoIP calls their Frame Relay WAN links can support. Each of their Frame Relay WAN links has 84 kbps of bandwidth available outside all other applications and overhead. How many G.729 calls using the 8 kbps codec and 20 byte sample size can be supported?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: C

8. You have been forwarded some questions by a prospective VoIP customer who would like to know the Cisco default sample size for the G.729 codec. What is it?

- A. 40 ms
- B. 30 ms
- C. 20 ms
- D. 10 ms

Answer: C

9. Examine the following PBX system parameters:

The calling side seizes the line by going off-hook on its E-lead and sends information as DTMF digits.

The voice path is 4-wires, and the voice enabled router is in another building from the PBX.

Select the correct set of commands to allow communication between a voice enabled router and a PBX.

- A. voice port 1/0/0
signal immediate-start
operation 4-wire
type 2
- B. voice-port 1/0/0
signal delay-dial
operation 4-wire
type 1
- C. voice port 1/0/0
signal wink-start
operation 4-wire
type 3
- D. voice port 1/0/0

signal immediate-start

operation 4-wire

type 4

Answer: A

10. Examine the example output.

Choose the command that will restore communication with gatekeeper functionality to this device.

A. h323-gateway voip h323-id GK1

B. gateway

C. h323-gateway voip bind srcaddr 172.16.2.2

D. h323-gateway voip GW1-zone2.abc.com abc.com ipaddr 172.16.2.1

Answer: B

11. Your customer has forwarded this diagram and configuration. The customer wishes to have a connection between its PBXs, a connection that is created and dropped as required. There is one configuration statement missing from each router. What are the two missing statements? (Choose two.)

A. connection trunk 2015551000404555....

B. connection trunk 4045551200

C. connection tie-line 4045551200

D. connection tie-line 404555....

E. connection tie-line 2015551000

F. connection trunk

Answer: CE

12. Which command parameter specifies that the router should not attempt to initiate a trunk connection but should wait for an incoming call before establishing the trunk?

A. codec clear-channel

B. connection-trunk 404555.... answer-mode

C. voice-port 1/0:1

D. ds0-group timeslots 1-23 type ext-sig

Answer: B

13. You are working with a potential customer that would like to integrate its existing PBX telephone system into its IP network. The accompanying figure shows that the customer has two offices that need to be connected to the IP network so that the customer can exchange telephone calls without using the PSTN. Both PBXs use a proprietary signaling type.

Which signaling type will allow you to support your customer?

A. E&M

B. CCS

C. CAS

D. T-CCS

E. FXO

F. FXS

Answer: D

14. You are meeting with a customer that has deployed IP telephony at their headquarters location. They would like to roll out IP telephony to their regional office as well. They are now using the G.711 codec at headquarters. They want to be able to maximize the number of calls carried without impacting voice quality or forcing a WAN upgrade. Which codec would be appropriate for their WAN?

A. G.726

B. G.723.1

C. G.711

D. G.729B

Answer: D

15. In a VoIP environment when speech samples are framed every 20 ms, a payload of 20 bytes is generated. What is the size of the combined IP, UDP, and RTP headers?

- A. 40 bytes
- B. 12 bytes
- C. 20 bytes
- D. 8 bytes
- E. 4 bytes
- F. 2 bytes

Answer: A

16. A customer would like to be able to retire their existing permanent PSTN trunk connection between their PBXs and migrate to permanent connections over the IP WAN. There is one configuration statement missing from each router in the figure. What are the two missing statements? (Choose two.)

- A. connection tie-line e&m
- B. connection trunk 4045551200
- C. connection tie-line 2015551000
- D. connection trunk 2015551000
- E. connection tie-line 4045551200
- F. connection tie-line

Answer: BD

[More 642-432 Information](#)

Related 642-432 Exams

[642-415](#) *Unified Communications Architecture and Design*

[642-444](#) *IP Telephony Exam (CIPT)*

[642-432](#) *Cisco Voice Over IP*

[642-162](#) *IP Contact Center Express Implementation Exam*

[644-141](#) *IP Communications CallManager Express Exam (CME)*

[642-143](#) *Communications IP Telephony Express Exam*

[642-144](#) *IP Telephony Express(IPTX)*

[642-104](#) *Unified Communication for System Engineers Exam*

[642-071](#) *Cisco Unity and Design Networking(CUDN)*

[642-414](#) *Communications Telephony Design Exam*

[646-229](#) *IP Communications Advanced Account Manager*

Other Cisco Exams

[640-822](#) [646-102](#) [352-001](#) [646-561](#) [642-066](#) [642-145](#) [350-001-](#) [642-372](#)

[LAB](#) [642-545](#)

[642-453](#) [642-821](#) [646-057](#) [642-541](#) [642-871](#) [642-832](#) [642-801](#) [646-967](#)

[642-241](#) [642-523](#) [642-291](#)