

## 642-522 CCSP

### Cisco Securing Networks with PIX and ASA Exam(SNPA)

**Practice Exam:** 642-522 Exams

**Exam Number/Code:** 642-522

**Exam Name:** Securing Networks with PIX and ASA Exam(SNPA)

**Questions and Answers:** 63 Q&As

( [CCSP](#) )



Exam : [642-522](#)

"Securing Networks with PIX and ASA Exam(SNPA)", also known as 642-522 exam, is a Cisco certification. With the complete collection of questions and answers, TestInside has assembled to take you through 63 Q&As to your 642-522 Exam preparation. In the 642-522 exam resources, you will cover every field and category in Cisco Certification helping to ready you for your successful Cisco Certification.

Quality and Value for the 642-522 Exam TestInside Practice Exams for Cisco **CCSP** Certification 642-522 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

#### ***TestInside provide the professional Q&A.***

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 642-522 Exam.

642-522 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the CCSP product experts, included the current newest 642-522 examination questions.

3. 100% Guarantee to Pass Your CCSP exam and get your CCSP Certification.

If you do not pass the Cisco Certification 642-522 exam (Securing Networks with PIX and ASA Exam(SNPA)) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

#### ***use TestInside 642-522 Q&A ensure you pass the exam at your first try.***

TestInside professional provide CCSP 642-522 the newest Q&A, completely covers 642-522 test original topic. With our complete CCSP resources, you will minimize your CCSP cost and be ready to pass your 642-522 tests on Your First Try, 100% Money Back Guarantee included!

[Cisco 642-522](#) Test belongs to one of the CCSP certified test, if needs to obtain the CCSP certificate, you also need to participate in other related test, the details you may visit the [CCSP](#) certified topic, in there, you will see all related CCSP certified subject of examination.

#### ***TestInside Testing Engine Features***

Comprehensive questions and answers about 642-522 exam

642-522 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

642-522 exam questions updated on regular basis

Same type as the certification exams, 642-522 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 642-522 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : Cisco 642-522

Title : Securing Networks with PIX and ASA Exam(SNPA)

1. Refer to the exhibit.

The network administrator for this small site has chosen to authenticate HTTP cut-through proxy traffic via a local database on the Cisco PIX Security Appliance. Which command strings should the administrator enter to accomplish this?

- A. `pix1(config)# static (dmz,outside) 192.168.16.6 172.16.16.6`  
`pix1(config)# access-list 150 permit tcp any host 172.16.16.6 eq www`  
`pix1(config)# aaa authentication match 150 outside LOCAL`
- B. `pix1(config)# static (dmz,outside) 192.168.16.6 172.16.16.6`  
`pix1(config)# access-list 150 permit tcp any host 192.168.16.6 eq www`  
`pix1(config)# aaa authentication match 150 outside pix1`
- C. `pix1(config)# static (dmz,outside) 192.168.16.6 172.16.16.6`  
`pix1(config)# access-list 150 permit tcp any host 172.16.16.6 eq www`  
`pix1(config)# aaa authentication match 150 outside pix1`
- D. `pix1(config)# static (dmz,outside) 192.168.16.6 172.16.16.6`  
`pix1(config)# access-list 150 permit tcp any host 192.168.16.6 eq www`  
`pix1(config)# aaa authentication match 150 outside LOCAL`

Answer: D

2. Refer to the exhibit.

Users on the DMZ are complaining that they cannot gain access to the insidehost via HTTP. What did the network administrator determine after reviewing the network diagram and partial configuration?

- A. The static (inside,dmz) command is not configured correctly.
- B. The global (dmz) command is not configured correctly.
- C. The nat (dmz) command is missing.
- D. The dmzin access list is not configured correctly.

Answer: D

3. Refer to the exhibit.

An administrator is configuring the failover link on the secondary unit, pix2 and needs to configure the IP addresses of the failover link. At pix2, which of these additional commands should be entered?

- A. `pix2(config)# failover lan ip 172.17.2.1 255.255.255.0 standby 172.17.2.7`
- B. `pix2(config)# failover link 172.17.2.7 255.255.255.0 standby 172.17.2.1`
- C. `pix2(config)# failover interface ip LANFAIL 172.17.2.1 255.255.255.0 standby 172.17.2.7`
- D. `pix2(config)# interface ethernet3`  
`pix2(config-if)# failover ip address 172.17.2.7 255.255.255.0 standby 172.17.2.1`

Answer: C

4. During failover, which security appliance attribute does not change?

- A. failover unit status-active and standby
- B. active and standby interfaces-IP address
- C. failover unit type-primary and secondary
- D. active and standby interfaces-MAC address

Answer: C

5. Refer to the exhibit.

An administrator wants to permanently map host addresses on the DMZ subnet to the same host addresses, but a different subnet, on the outside interface. Which command should the administrator use to accomplish this?

- A. NAT (dmz) 0 172.16.1.0 netmask 255.255.255.0
- B. access-list server\_map permit tcp any 192.168.10.0 255.255.255.0  
Nat (outside) 10 access-list server\_map  
Global (dmz) 10 172.16.1.9-10 netmask 255.255.255.0
- C. static (dmz,outside) 192.168.10.0 172.16.1.0 netmask 255.255.255.0
- D. NAT (dmz) 1 172.16.1.0 netmask 255.255.255.0  
Global (outside) 1 192.168.10.9-10 netmask 255.255.255.0

Answer: C

6. Which is a method of identifying the traffic requiring authorization on the security appliance?

- A. implicitly enabling TACACS+ authorization rules in the response packet
- B. specifying ACLs that authorization rules must match
- C. independently interpreting authorization rules before authentication has occurred to decrease overall AAA processing time
- D. checking the authentication rules for a match thus allowing the traffic to be authorized

Answer: B

7. Refer to the exhibit.

This security appliance is configured for what two types of failover? (Choose two.)

- A. unit-based failover
- B. LAN cable-based failover
- C. stateful failover
- D. Active/Standby failover
- E. Active/Active failover
- F. Context/Group failover

Answer: BE

8. The ASDM client is supported on which PC operating systems? Choose the best answer.

- A. Windows, Macintosh, and Linux
- B. Windows and Sun Solaris
- C. Windows, Linux, and Sun Solaris
- D. Windows and Linux

Answer: C

9. What is displayed as a result of entering the command syntax show aaa-server group1 host 192.1630.60 in the security appliance?

- A. aaa-server configuration for a particular host in server group group1
- B. aaa-server statistics for a particular host in server group group1
- C. aaa-server configuration for server group group1
- D. aaa-server statistics for the host group1 at IP address 192.168.30.60

Answer: B

10. When an outside FTP client accesses a corporation's dmz FTP server through a security appliance, the administrator wants the security appliance to restrict ftp commands that can be performed by the client. Which security appliance commands enable the administrator to restrict the ftp client to performing a specific set of ftp commands.

- A. ftp-map inbound\_ftp  
request-cmd deny appe dele rmd
- B. ftp-map inbound\_ftp

```
request-cmd permit get put cdup
```

C. policy-map inbound

```
class inbound_ftp_traffic
```

```
inspect ftp strict get put cdup
```

D. policy-map inbound

```
class inbound_ftp_traffic
```

```
inspect ftp strict appe dele rmd
```

Answer: A

11. Refer to the exhibit.

Given the configuration, what traffic will be logged to the AAA server?

A. All connection information will be logged in the accounting database.

B. All outbound connection information will be logged in the accounting database.

C. Only the authenticated console connection information will be logged in the accounting database.

D. This is not a valid configuration because TACACS+ connection information cannot be captured and logged.

Answer: B

12. An administrator is defining a modular policy. As part of the policy, the administrator wants to define a traffic flow between Internet hosts and a specific web server on the DMZ. Which commands should the administrator use?

A. class-map http\_traffic

```
match port tcp eq www
```

B. class-map http\_traffic

```
match flow ip destination address 192.168.1.11
```

C. class-map http\_traffic

```
match set 192.168.1.11
```

D. access-list 150 permit tcp any host 192.168.1.11 eq www

```
class-map http_traffic
```

```
match access-list 150
```

Answer: D

13. The inline IPS software feature set is available in which security appliances?

A. any Cisco PIX and ASA Security Appliance running v.7 software and an AIP-SSM module

B. only Cisco PIX 515, 525, and 535 Security Appliances with an AIP-SSM module

C. only Cisco ASA 5520 and 5540 Security Appliances with an AIP-SSM module

D. any Cisco ASA 5510, 5520, or 5540 Security Appliance with an AIP-SSM module

Answer: D

14. Refer to the exhibit.

An administrator wants a user on the inside network to access two sites on the Internet and present two different source IP addresses. When the user is accessing Company A web servers, the source IP address is translated to 192.168.0.9. When the user is accessing Company B web servers, the source address is translated to 192.168.0.21.

Which of these can the security appliance administrator configure to accomplish this application?

A. inside NAT

B. identity NAT

C. static

D. policy NAT

Answer: D

15. Refer to the exhibit.

When accessing the IPS icon in ASDM, the administrator is presented with a "Connecting to IPS" popup window. In the window, the management IP address A.B.C.D is displayed where A.B.C.D is an actual IP address.

What is IPS management "connecting to" which has an IP address of A.B.C.D?

A. the AIP-SSM IPS control channel IP address

- B. the AIP-SSM IPS data channel IP address
- C. the AIP-SSM external interface IP address
- D. the AIP-SSM HTTP server virtual address

Answer: C

[More 642-522 Information](#)

**Related 642-522 Exams**

[642-515](#) *Securing Networks with ASA Advanced*

[642-545](#) *Implementing Cisco Security Monitoring, Analysis and Response System*

[642-542](#) *Cisco SAFE Implementation Exam*

[642-552](#) *Securing Cisco Network Devices Exam*

[642-513](#) *Securing Hosts Using Cisco Security Agent Exam (HIPS)*

[642-502](#) *Securing Networks with Cisco Routers and Switches Exam (SNRS)*

[642-503](#) *Securing Networks with Cisco Routers and Switches*

[642-523](#) *Securing Networks with PIX and ASA*

[642-532](#) *Securing Networks Using Intrusion Prevention Systems Exam (IPS)*

[642-521](#) *Cisco Secure PIX Firewall Advanced*

[642-551](#) *Securing Cisco Network Devices Exam (SND)*

[642-522](#) *Securing Networks with PIX and ASA Exam (SNPA)*

**Other Cisco Exams**

<a href="#"><u>642-321</u></a>	<a href="#"><u>642-736</u></a>	<a href="#"><u>642-821</u></a>	<a href="#"><u>646-202</u></a>	<a href="#"><u>642-444</u></a>	<a href="#"><u>642-311</u></a>	<a href="#"><u>640-460</u></a>	<a href="#"><u>646-361</u></a>
<a href="#"><u>646-574</u></a>	<a href="#"><u>642-342</u></a>	<a href="#"><u>642-104</u></a>	<a href="#"><u>642-982</u></a>	<a href="#"><u>646-391</u></a>	<a href="#"><u>642-054</u></a>	<a href="#"><u>642-811</u></a>	<a href="#"><u>642-871</u></a>
<a href="#"><u>642-243</u></a>	<a href="#"><u>642-873</u></a>	<a href="#"><u>646-151</u></a>	<a href="#"><u>642-356</u></a>				