

642-691 CCIP

Cisco CCIP BGP + MPLS Exam (BGP + MPLS)

Practice Exam: 642-691 Exams

Exam Number/Code: 642-691

Exam Name: CCIP BGP + MPLS Exam (BGP + MPLS)

Questions and Answers: 80 Q&As

([CCIP](#))



Exam : [642-691](#)

"CCIP BGP + MPLS Exam (BGP + MPLS)", also known as 642-691 exam, is a Cisco certification. With the complete collection of questions and answers, TestInside has assembled to take you through 80 Q&As to your 642-691 Exam preparation. In the 642-691 exam resources, you will cover every field and category in Cisco Certification helping to ready you for your successful Cisco Certification.

Quality and Value for the 642-691 Exam TestInside Practice Exams for Cisco **CCIP** Certification 642-691 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

TestInside provide the professional Q&A.

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 642-691 Exam.

642-691 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the CCIP product experts, included the current newest 642-691 examination questions.

3. 100% Guarantee to Pass Your CCIP exam and get your CCIP Certification.

If you do not pass the Cisco Certification 642-691 exam (CCIP BGP + MPLS Exam (BGP + MPLS)) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

use TestInside 642-691 Q&A ensure you pass the exam at your first try.

TestInside professional provide CCIP 642-691 the newest Q&A, completely covers 642-691 test original topic. With our complete CCIP resources, you will minimize your CCIP cost and be ready to pass your 642-691 tests on Your First Try, 100% Money Back Guarantee included!

[Cisco 642-691](#) Test belongs to one of the CCIP certified test, if needs to obtain the CCIP certificate, you also need to participate in other related test, the details you may visit the [CCIP](#) certified topic, in there, you will see all related CCIP certified subject of examination.

TestInside Testing Engine Features

Comprehensive questions and answers about 642-691 exam

642-691 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

642-691 exam questions updated on regular basis

Same type as the certification exams, 642-691 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 642-691 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : Cisco 642-691

Title : Cisco CCIP BGP + MPLS Exam (BGP + MPLS)

1. Refer to the exhibit. Which two of the following statements about the MPLS configurations are true? (Choose two.)

- A. The VPI range being configured is the default VPI range.
- B. The router is missing the mpls label protocol ldp configuration command on its ATM 0/0.1 subinterface to make it an LC-ATM enabled subinterface.
- C. There is a problem with the configurations because the control VC should be set to 0 32 instead.
- D. The ATM switch is using VC merge since VC merge is enabled by default.
- E. For MPLS label allocations, both VPI 6 and 7 can be used.

Answer: DE

2. Which two statements about a transit AS are correct? (Choose two.)

- A. A transit AS has eBGP connection(s) to only one external AS.
- B. Routes between ASs are always exchanged via eBGP.
- C. A transit AS uses an IGP like OSPF or ISIS to propagate the external networks within the transit AS.
- D. Core routers within a transit AS normally use default routing to reach the external networks.
- E. iBGP sessions can be established between non directly connected routers.

Answer: BE

3. Which command is used to configure the external, confederation-wide AS number?

- A. `router(config)#router bgp {as-number}`
- B. `router(config-router)#bgp confederation peers {as-number}`
- C. `router(config-router)#bgp confederation identifier {as-number}`
- D. `router(config-router)#bgp cluster-id {as-number}`
- E. `router(config-router)#neighbor {ip address} remote-as {as-number}`

Answer: C

4. Based on the topology diagram shown in the exhibit, when should BGP be used as the routing protocol between the customer and the ISP?

- A. If physical link failures can not be detected by the link-level procedures.
- B. If the customer wants to affect how the ISP will route the customer's traffic out to the rest of the Internet.
- C. If the ISP does not support static routing with the customer.
- D. If the customer is using provider-assigned (PA) addresses inside the customer's network.
- E. If the customer is using private addresses inside the customer's network.

Answer: A

5. Which show command can be used to display the originator ID and cluster-list?

- A. `show ip bgp`
- B. `show ip bgp sum`
- C. `show ip route bgp`
- D. `show ip route {prefix}`
- E. `show ip bgp {prefix}`
- F. `show ip bgp neighbors {ip address}`

Answer: E

6. Based on the network diagram shown in the exhibit, what is the correct configuration on the customer edge router used to conditionally announce the customer networks to the ISP?

A. router bgp 65001

! neighbor commands not shown

network 192.168.8.0 mask 255.255.252.0

!

ip route 192.168.8.0 255.255.252.0 192.168.8.33

B. router bgp 65001

! neighbor commands not shown

aggregate-address 192.168.8.0 255.255.252.0 summary-only

!

ip route 192.168.8.0 255.255.252.0 192.168.8.33

C. router bgp 65001

! neighbor commands not shown

network 192.168.8.0

network 192.168.9.0

network 192.168.10.0

network 192.168.11.0

!

ip route 192.168.8.0 255.255.255.0 null0

ip route 192.168.9.0 255.255.255.0 null0

ip route 192.168.10.0 255.255.255.0 null0

ip route 192.168.11.0 255.255.255.0 null0

D. router bgp 65001

! neighbor commands not shown

aggregate-address 192.168.8.0 255.255.252.0 summary-only

!

router ospf 1

network 192.168.8.0 0.0.3.255 area 0

E. router bgp 65001

! neighbor commands not shown

aggregate-address 192.168.8.0 255.255.252.0

!

ip route 192.168.8.0 255.255.252.0 null0

Answer: A

7. As the penalty for a flapping route decreases and falls below a certain limit, the route is unsuppressed. What is the name of that limit?

A. half-life limit

B. suppress limit

C. max-suppress-time limit

D. reuse limit

E. unsuppress limit

F. penalty limit

Answer: D

8. Refer to the diagram. What problem can be caused by the second P router summarizing the loopback address of the egress PE router?

A. The first P router will be faced with a VPN label which it does not understand.

B. The second P router will be faced with a VPN label which it does not understand.

C. The egress PE router will not be able to establish a label switch path (LSP) to the ingress PE router.

D. A label switch path (LSP) will be established from the ingress PE router to the egress PE router, an event that is not desirable.

E. The ingress PE router will not be able to receive the VPN label from the egress PE router via MP-IBGP.

Answer: B

9. Which two of the following statements regarding LDP are true? (Choose two.)

- A. LDP can also be used between nonadjacent routers using multicast LDP hello messages.
- B. LDP does not require periodic hello messages once the LDP session has been established between the LDP peers.
- C. LDP hello messages use TCP packets with a destination port number of 646.
- D. Multiple sessions can be established between a pair of LSRs if they use multiple label spaces.
- E. Per-platform label space can be identified by a label space ID of 0 in the LDP identifier field.

Answer: DE

10. In a central services topology, which routes do client VRFs contain?

- A. routes from the client site, but not from the server site
- B. routes from the server site, but not from the client site
- C. routes from both the client site and the server site
- D. only EBGP routes from either the client site or the server site

Answer: C

11. For which purpose is the command `mpls ldp maxhops` used?

- A. In large ATM-MPLS networks, the LFIB can become too large and it may be necessary to limit the maximum diameter of the MPLS LSPs.
- B. Because downstream-on-demand label allocation uses hop count to control loop detection, it maybe necessary to limit the maximum diameter of the MPLS network.
- C. Because end-to-end delay can cause problems with some voice applications, it may be necessary to limit the maximum diameter of the MPLS network.
- D. When interconnecting large frame mode MPLS and cell mode networks it may be necessary to limit the maximum network diameter to prevent forwarding loops.

Answer: B

12. On a dedicated subinterface implementation, PE-2 must establish an address-family vrf IPv4 BGP neighbor relationship with which router?

- A. CE-1
- B. CE-2
- C. PE-1
- D. PE-IG
- E. CE-1 and CE-2
- F. PE-1 and PE-IG

Answer: B

13. Based on the network diagram shown in the exhibit, both R5 and R6 are clients of the R2 RR. When the 10.0.0.0/8 iBGP update from R3 is received by the R2 RR, which router(s) will R2 reflect the update to?

- A. R1 only
- B. R5 and R6
- C. R5, R6 and R1
- D. R4, R5 and R6
- E. R4, R5, R6 and R1
- F. to no other router

Answer: C

14. What are three drawbacks of a peer-to-peer VPN using a shared provider edge (PE) router? (Choose three.)

- A. A full mesh of virtual circuits is required between the customer sites.
- B. All the customers have to share a common IP address space.

- C. Optimal routing between customer sites cannot be guaranteed.
- D. The shared PE router has to know all routes for all customers.
- E. Packet filters are required on the PE routers.

Answer: BDE

15. What does the following command accomplish? `sanjose#clear ip bgp 10.1.1.1 in prefix-filter`

- A. The sanjose router will perform an outbound soft reconfig to the 10.1.1.1 neighbor.
- B. The sanjose router will send out the ORF prefix-list so that a new route refresh will be received from the 10.1.1.1 neighbor.
- C. The 10.1.1.1 router will perform an inbound soft reconfig on the updates from the sanjose neighbor.
- D. The 10.1.1.1 router will send out the ORF prefix-list so that a new route refresh will be received from the sanjose neighbor.
- E. The bgp session between the sanjose and the 10.1.1.1 router will be reset so that all the new bgp updates from the 10.1.1.1 router can be processed by the inbound prefix-list at the sanjose router.
- F. The bgp session between the sanjose and the 10.1.1.1 router will be reset so that all the new bgp updates from the sanjose router can be processed by the inbound prefix-list at the 10.1.1.1 router.

Answer: B

[More 642-691 Information](#)

Related 642-691 Exams

[642-642](#) *Quality of Service (QoS)*

[642-691](#) *CCIP BGP + MPLS Exam (BGP + MPLS)*

[642-661](#) *CCIP Configuring BGP on Cisco Routers (BGP)*

[642-611](#) *CCIP Implementing Cisco MPLS Exam (MPLS)*

Other Cisco Exams

[642-061](#) [642-105](#) [642-432](#) [642-971](#) [642-091](#) [642-591](#) [642-533](#) [642-813](#)

[640-721](#) [642-567](#) [642-504](#) [642-542](#) [642-801](#) [646-985](#) [642-274](#) [642-871](#)

[642-311](#) [350-025](#) [646-976](#) [642-112](#)