

HP0-648 HP AIS Certification II HP Adaptive EDGE Fundamentals

Practice Exam: HP0-648 Exams

Exam Number/Code: HP0-648

Exam Name: Adaptive EDGE Fundamentals

Questions and Answers: 71 Q&As

([HP AIS Certification II](#))



Exam : [HP0-648](#)

"Adaptive EDGE Fundamentals", also known as HP0-648 exam, is a HP certification. With the complete collection of questions and answers, TestInside has assembled to take you through 71 Q&As to your HP0-648 Exam preparation. In the HP0-648 exam resources, you will cover every field and category in HP Certification helping to ready you for your successful HP Certification.

Quality and Value for the HP0-648 Exam TestInside Practice Exams for HP **HP AIS Certification II** Certification HP0-648 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

TestInside provide the professional Q&A.

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the HP0-648 Exam.

HP0-648 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the HP AIS Certification II product experts, included the current newest HP0-648 examination questions.

3. 100% Guarantee to Pass Your HP AIS Certification II exam and get your HP AIS Certification II Certification.

If you do not pass the HP Certification HP0-648 exam (Adaptive EDGE Fundamentals) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

use TestInside HP0-648 Q&A ensure you pass the exam at your first try.

TestInside professional provide HP AIS Certification II HP0-648 the newest Q&A, completely covers HP0-648 test original topic. With our complete HP AIS Certification II resources, you will minimize your HP AIS Certification II cost and be ready to pass your HP0-648 tests on Your First Try, 100% Money Back Guarantee included!

[HP HP0-648](#) Test belongs to one of the HP AIS Certification II certified test, if needs to obtain the HP AIS Certification II certificate, you also need to participate in other related test, the details you may visit the [HP AIS Certification II](#) certified topic, in there, you will see all related HP AIS Certification II certified subject of examination.

TestInside Testing Engine Features

Comprehensive questions and answers about HP0-648 exam

HP0-648 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

HP0-648 exam questions updated on regular basis

Same type as the certification exams, HP0-648 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free HP0-648 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : HP HP0-648

Title : ProCurve Adaptive Edge Fundamentals

1. You are installing a new HP ProCurve switch at a customer site. Which statements describe procedures for configuring the switch's IP addressing information? Select TWO.

- A. Connect to the switch using the serial console interface, enter the global configuration level, enable DHCP, and assign an address scope.
- B. Connect to the switch using the serial console interface, enter the global configuration level, and assign a box-wide IP address and mask.
- C. Connect to the switch using the serial console interface, enter the global configuration level, and assign an IP address and mask within the VLAN 1 context configuration level.
- D. Leave the switch at its default settings and allow it to acquire a reserved IP address, mask, and default gateway from a DHCP server.
- E. Connect to the switch using the Telnet interface, enter the global configuration level, and assign a box-wide IP address.

Answer: CD

2. You are configuring an HP ProCurve 5300xl switch that will act as a default gateway for devices in VLAN 70. What configuration steps are necessary to enable the switch to perform this function? Select TWO.

- A. Add the switch's uplink ports to VLAN 70.
- B. Assign an IP address to the switch's VLAN 70 interface.
- C. Enable IP routing.
- D. Configure all ports that are members of VLAN 70 as tagged.
- E. Configure the switch with a default gateway.

Answer: BC

3. You are assigned to configure HP ProCurve switches at a customer site for in-band management. Which of the following are in-band management methods? Select TWO.

- A. SNMP
- B. XMODEM
- C. serial console
- D. Telnet
- E. menu interface

Answer: AD

4. You need to configure VLANs on an HP ProCurve 5300xl switch that is currently set to factory defaults. You issue the CLI command

```
no vlan 1 untagged a1-a4
```

What will the result of this command be?

- A. Ports a1-a4 will be removed from VLAN 1.
- B. You will receive an error saying you cannot remove the ports from VLAN 1.
- C. The ports will become tagged members of VLAN 1.
- D. You will receive a prompt asking which VLAN the ports should be assigned to.

Answer: B

5. You are going to install and configure HP ProCurve switches in a network that includes a core switch manufactured

by Cisco Systems, Inc. What VLAN configuration step is necessary to ensure compatibility with the native VLAN on the Cisco switch?

- A. Configure the VLAN for untagged status on the HP ProCurve switches.
- B. Configure the VLAN as the default VLAN on the HP ProCurve switches.
- C. Configure GARP VLAN Registration Protocol on the HP ProCurve switches.
- D. Configure the VLAN for management access to the HP ProCurve switches.

Answer: A

6. While troubleshooting a network outage, you decide to examine the Event log of an HP ProCurve Switch 5348xl. Identify the command that filters reports of normal behavior from the console display.

- A. console events -n
- B. console events critical
- C. console events not-info
- D. console events -c

Answer: C

7. A network administrator asks you about the differences in the discovery features of HP ProCurve Manager and HP ProCurve Manager Plus. Which statement describes these differences?

- A. There is no difference between the discovery processes used by the two applications.
- B. HP ProCurve Manager Plus enables the scheduling of auto-discovery. HP ProCurve Manager requires users to initiate discovery manually.
- C. HP ProCurve Manager Plus will discover devices from manufacturers other than HP. HP ProCurve Manager will discover only ProCurve devices.
- D. HP ProCurve Manager Plus supports discovery based on CDP and FDP. HP ProCurve Manager does not support discovery based on FDP.

Answer: A

8. You have been asked to install and configure HP ProCurve switches in a network that includes switches manufactured by Cisco Systems, Inc. During a planning session, the network's administrator repeatedly refers to the "access ports" on the Cisco switches. What is an equivalent term or feature on HP ProCurve switches?

- A. edge ports
- B. untagged ports
- C. uplink ports
- D. trunk ports

Answer: B

9. How does an IP host determine which destination addresses are local and which are remote?

- A. The host derives a range of local addresses by applying its configured subnet mask to its own IP address.
- B. The host broadcasts an ICMP request to its local router and requests a hop-by-hop path.
- C. The host broadcasts an ICMP request to all routers in the enterprise and requests a hop-by-hop path.
- D. The host creates and maintains a table that lists remote address ranges and the next hop router for each range.

Answer: A

10. A network administrator at a customer site asks about the impact of classifying some high-priority traffic for an 802.1p value of 7 and other traffic for an 802.1p value of 6. What will the effect of this configuration be? The change in 802.1p value _____.

- A. is not possible because the 802.1p field does not support a value of 7
- B. will introduce network latency by making forwarding more complicated
- C. will provide more granular control over forwarding priority
- D. will make no difference in actual forwarding because both priorities are placed in the same physical queue on switches before forwarding

Answer: D

11. You have been asked to configure IGMP on an HP ProCurve Switch 5348xl at a customer site. While planning the configuration, you determine that the network does not currently include an IGMP Querier. To act as IGMP Querier, the switch must be configured with _____.

- A. an IP address for each VLAN that will support multicasting
- B. a Class D IP address
- C. 802.1p prioritization settings for each VLAN that will support multicasting
- D. a box-wide default gateway

Answer: A

12. You have just finished configuring Multiple Spanning Tree (MST) on HP ProCurve 5348xl switches at a customer site. While checking your configuration, you notice that two switches have declared themselves to be the Root in one MST instance. How can you correct this configuration error? Reconfigure the _____.

- A. bridge priority on one of the switches
- B. switches so that they have the same configuration name and revision number
- C. VLAN assignments on the switches
- D. port priorities on the links between the switches

Answer: B

13. You are assigned to a team that is designing a new HP ProCurve solution. The team soon will begin work on diagramming the network's physical connectivity. What is the appropriate phase of the design process for this activity?

- A. assess customer needs
- B. develop and propose a solution
- C. implement and document the solution
- D. it can be done in any phase

Answer: B

14. You have been sent to install and configure HP ProCurve switches on a network that already includes switches manufactured by Cisco Systems, Inc. During planning meetings, the network administrator often refers to "trunk ports." What does the administrator mean?

- A. ports that connect the distribution and core layers
- B. ports that are configured for gigabit connectivity
- C. ports that are aggregated into a single logical port
- D. ports that carry multiple VLANs

Answer: D

15. You have configured port a1 on an HP ProCurve switch as an untagged member of VLAN 20. The port is not a member of any other VLANs. Which statement describes an action the switch takes when forwarding a frame through port a1?

- A. The switch adds a tag that will be interpreted by the device connected to that port.
- B. The switch strips any tag that may have been included with the frame when it was received.
- C. HP switches require tagged status on all ports.
- D. The switch changes the VLAN ID of any tag to 20.

Answer: B

[More HP0-648 Information](#)

Related HP0-648 Exams

[HP0-S20](#) *Implementing HP BladeSystem*

[HP2-T11](#) *Industry Standard Architecture and Technology*

[HP0-216](#) *Enterprise Systems Management*

[HP0-J25](#) *HP StorageWorks AIS 2008 Delta Exam*

[HP0-648](#) *Adaptive EDGE Fundamentals*

[HP0-683](#) *Implementing HP ProLiant Servers*

[HP0-S23](#) *Design & Implementation of HP Systems Insight Manager v5.3*

[HP0-402](#) *Implementing HP Enterprise Virtual Array Solutions*

[HP0-553](#) *Servicing HP Entry-level Integrity Servers*

[HP0-M30](#) *HP Network Node Manager Essentials*

[HP2-Z05](#) *Selling the HP ProCurve Portfolio*

Other HP Exams

[HP0-782](#) [HP0-Y19](#) [HP0-753](#) [HP0-626](#) [HP0-071](#) [HP0-198](#) [HP0-Y23](#) [HP0-058](#)

[HP0-P16](#) [HP0-064](#) [HP0-429](#) [HP0-S17](#) [HP0-X02](#) [HP0-286](#) [HP0-J29](#) [HP0-P10](#)

[HP0-M28](#) [HP0-785](#) [HP0-052](#) [HP0-727](#)