

**Exam** : [Juniper JN0-202](#)

**Title** : **M-series, Associate  
(JNCIA-M)**

**Version** : **Demo**

1. Which command allows real-time monitoring of interface statistics on interface so-0/0/0?

- A. monitor interface so-0/0/0
- B. monitor traffic interface so-0/0/0
- C. monitor statistics so-0/0/0
- D. monitor so-0/0/0

**Answer: A**

2. Which command can be used to display information about packets that have been logged with the log firewall filter action?

- A. show log
- B. show log messages
- C. show firewall
- D. show firewall log

**Answer: D**

3. To create a stable IBGP peering arrangement, it is recommended that internal peering be created between the loopback interfaces of the IBGP peering routers. Why is the local-address command required for successful connectivity in this scenario?

- A. to send the BGP Open message
- B. to tell the local router which interface the update is going to be received on
- C. to tell the local router which interface to source the update from
- D. to authenticate using MD5 between these neighbors

**Answer: C**

4. How can you identify all routes that are more specific than 10. 0/16, excluding the exact match?

- A. route-filter 10. 0/16 longer
- B. route-filter 10. 0. 0/17 longer
- C. route-filter 10. 0/16 orlonger
- D. route-filter 10. 0. 0/17 upto /32

**Answer: A**

5. Which router feature will improve Routing Engine fail-over times?

- A. GRES
- B. RED
- C. MPLS
- D. VRRP

**Answer: A**

6. Given the following policy:

```
policy-statement limit-cust {  
  from { route-filter 192. 168. 0. 0/16 orlonger accept;  
         route-filter 192. 168. 8. 0/21 longer;  
         route-filter 192. 168. 0. 0/24 orlonger {  
           metric 5;  
         }  
         reject;  
       }  
  then {  
    metric 10; accept;  
  }  
}
```

What happens to the route 192. 168. 9/24?

- A. The metric is set to 10, and the route is accepted.
- B. The metric is set to 5, and the route is rejected.
- C. The route is accepted.
- D. The route passes through this filter to the next.

**Answer: A**

7. Which RSVP object allows for loop avoidance in the downstream direction?

- A. Record Route Object in Path Message
- B. Record Route Object in Reservation Message
- C. Tspec Object in Reservation Message

#### D. Session Attribute Object in Path Message

**Answer: A**

8. Given the following configuration:

```
interfaces {
  so-0/0/0 {
    unit 0 {
      family inet {
        address 10. 10. 10. 1/24;
      }
    }
  }
  so-0/0/1 {
    unit 0 {
      family inet {
        address 20. 20. 20. 1/24;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 192. 168. 1. 1/32;
      }
    }
  }
}
```

What is considered an exception packet?

- A. ICMP traceroute packet with TTL set to 5
- B. ICMP echo request addressed to 192. 168. 1. 1
- C. IP packet addressed to 192. 168. 100. 100
- D. IP packet addressed to 10. 100. 100. 10

**Answer: B**

9. Which two statements are true about a T-Series Packet Forwarding Engine? (Choose two. )

- A. Only one PFE is allowed per chassis.
- B. Multiple PFEs are allowed per chassis.

- C. PFEs contain multiple ASICs on different boards.
- D. All PFE ASICs are on the FPC.

**Answer:** BC

10. Two Level 2 routers are exchanging Hello packets with different Area IDs. What occurs between these routers?

- A. An Adjacency forms.
- B. An Adjacency does not form.
- C. An Adjacency forms but traffic is not forwarded.
- D. No IS-IS PDUs are sent.

**Answer:** A

11. What are three characteristics of RIP? (Choose three. )

- A. RIP uses Bellman-Ford algorithm.
- B. RIP uses hop count as the metric.
- C. RIP supports maximum allowable hop count of 15.
- D. RIP floods updates to all RIP routers in the network.
- E. RIP sends updates only when a route metric changes.

**Answer:** ABC

12. Which version of IGMP is used by default on Juniper Networks routers?

- A. version 1
- B. version 2
- C. version 3
- D. version 4

**Answer:** B

13. By default, which routes have a more desirable route preference than OSPF?

- A. IS-IS
- B. BGP

- C. static
- D. aggregate

**Answer: C**

14. In the M7i or M10i which board functions as a combined Flexible PIC Concentrator and System Control Board?

- A. SFM
- B. cFEB
- C. RE
- D. FIC

**Answer: B**

15. Which CLI command displays routes advertised to an EBGP peer?

- A. show bgp received routes <neighbor>
- B. show bgp advertised routes <neighbor>
- C. show route receive-protocol bgp <neighbor>
- D. show route advertising-protocol bgp <neighbor>

**Answer: D**